

# Ground Flat Steel: S-7

## Oversize

| PART NUMBER    | THICKNESS   | WIDTH (in)  | 18" Long     | 36" Long     |
|----------------|-------------|-------------|--------------|--------------|
|                |             |             | WEIGHT (lbs) | WEIGHT (lbs) |
| 10S7-.125-.5   | <b>1/8</b>  | 1/2         | 0.36         | 0.73         |
| 10S7-.125-.75  |             | 3/4         | 0.54         | 1.08         |
| 10S7-.125-1    |             | 1           | 0.72         | 1.43         |
| 10S7-.125-1.25 |             | 1-1/4       | 0.89         | 1.79         |
| 10S7-.125-1.5  |             | 1-1/2       | 1.07         | 2.14         |
| 10S7-.125-2    |             | 2           | 1.43         | 2.85         |
| 10S7-.125-2.5  |             | 2-1/2       | 1.78         | 3.56         |
| 10S7-.125-3    |             | 3           | 2.13         | 4.27         |
| 10S7-.125-4    |             | 4           | 2.84         | 5.69         |
| 10S7-.125-5    |             | 5           | 3.55         | 7.10         |
| 10S7-.125-6    |             | 6           | 4.26         | 8.52         |
| 10S7-.156-.5   |             | <b>5/32</b> | 1/2          | 0.45         |
| 10S7-.156-.75  | 3/4         |             | 0.66         | 1.33         |
| 10S7-.156-1    | 1           |             | 0.88         | 1.76         |
| 10S7-.156-1.25 | 1-1/4       |             | 1.10         | 2.20         |
| 10S7-.156-1.5  | 1-1/2       |             | 1.32         | 2.63         |
| 10S7-.156-2    | 2           |             | 1.75         | 3.50         |
| 10S7-.156-2.5  | 2-1/2       |             | 2.19         | 4.37         |
| 10S7-.156-3    | 3           |             | 2.62         | 5.24         |
| 10S7-.156-4    | 4           |             | 3.49         | 6.98         |
| 10S7-.187-.5   | <b>3/16</b> |             | 1/2          | 0.53         |
| 10S7-.187-.75  |             | 3/4         | 0.79         | 1.57         |
| 10S7-.187-1    |             | 1           | 1.04         | 2.09         |
| 10S7-.187-1.25 |             | 1-1/4       | 1.30         | 2.60         |
| 10S7-.187-1.5  |             | 1-1/2       | 1.56         | 3.12         |
| 10S7-.187-2    |             | 2           | 2.07         | 4.15         |
| 10S7-.187-2.5  |             | 2-1/2       | 2.59         | 5.18         |
| 10S7-.187-3    |             | 3           | 3.10         | 6.21         |
| 10S7-.187-4    | 4           | 4.13        | 8.27         |              |
| 10S7-.25-.5    | <b>1/4</b>  | 1/2         | 0.69         | 1.39         |
| 10S7-.25-.75   |             | 3/4         | 1.03         | 2.06         |
| 10S7-.25-1     |             | 1           | 1.37         | 2.74         |
| 10S7-.25-1.25  |             | 1-1/4       | 1.71         | 3.42         |
| 10S7-.25-1.5   |             | 1-1/2       | 2.05         | 4.09         |
| 10S7-.25-1.75  |             | 1-3/4       | 2.38         | 4.77         |
| 10S7-.25-2     |             | 2           | 2.72         | 5.44         |
| 10S7-.25-2.5   |             | 2-1/2       | 3.40         | 6.80         |
| 10S7-.25-3     |             | 3           | 4.07         | 8.15         |
| 10S7-.25-4     |             | 4           | 5.43         | 10.85        |

**Thickness Tolerance: +.010/+.015**

**Width Tolerance: +.010/+.015**

**Length Tolerance: Plus**

| PART NUMBER    | THICKNESS   | WIDTH (in) | 18" Long     | 36" Long     |
|----------------|-------------|------------|--------------|--------------|
|                |             |            | WEIGHT (lbs) | WEIGHT (lbs) |
| 10S7-.312-.5   | <b>5/16</b> | 1/2        | 0.86         | 1.72         |
| 10S7-.312-.75  |             | 3/4        | 1.28         | 2.55         |
| 10S7-.312-1    |             | 1          | 1.70         | 3.39         |
| 10S7-.312-1.25 |             | 1-1/4      | 2.11         | 4.23         |
| 10S7-.312-1.5  |             | 1-1/2      | 2.53         | 5.07         |
| 10S7-.312-2    |             | 2          | 3.37         | 6.74         |
| 10S7-.312-2.5  |             | 2-1/2      | 4.21         | 8.41         |
| 10S7-.312-3    |             | 3          | 5.04         | 10.09        |
| 10S7-.312-4    | 4           | 6.72       | 13.44        |              |
| 10S7-.375-.5   | <b>3/8</b>  | 1/2        | 1.02         | 2.05         |
| 10S7-.375-.75  |             | 3/4        | 1.52         | 3.04         |
| 10S7-.375-1    |             | 1          | 2.02         | 4.04         |
| 10S7-.375-1.25 |             | 1-1/4      | 2.52         | 5.04         |
| 10S7-.375-1.5  |             | 1-1/2      | 3.02         | 6.04         |
| 10S7-.375-1.75 |             | 1-3/4      | 3.52         | 7.04         |
| 10S7-.375-2    |             | 2          | 4.02         | 8.04         |
| 10S7-.375-2.5  |             | 2-1/2      | 5.02         | 10.03        |
| 10S7-.375-3    |             | 3          | 6.01         | 12.03        |
| 10S7-.375-4    |             | 4          | 8.01         | 16.02        |
| 10S7-.5-.75    | <b>1/2</b>  | 3/4        | 2.01         | 4.03         |
| 10S7-.5-1      |             | 1          | 2.67         | 5.35         |
| 10S7-.5-1.25   |             | 1-1/4      | 3.33         | 6.67         |
| 10S7-.5-1.5    |             | 1-1/2      | 3.99         | 7.99         |
| 10S7-.5-2      |             | 2          | 5.31         | 10.63        |
| 10S7-.5-2.5    |             | 2-1/2      | 6.63         | 13.27        |
| 10S7-.5-3      |             | 3          | 7.96         | 15.91        |
| 10S7-.5-4      |             | 4          | 10.60        | 21.19        |