


# Square Wire Carbon Steel Die & Fixture Springs



12-INCH LENGTHS - PLAIN ENDS									
Hole Dia.	Rod Dia.	Stock No.	Wire Size	Space Between Coils	Max Safe Load Lbs.	Total Coils	PSI of Compression	Approx. Solid Height	No. per Box
.375	.187	SR-0	0.062	.047	25.00	111	12½	7.50	12
.437	.250	SR-1A	0.062	.078	40.00	86	9	5.67	12
.500	.250	SR-1B	0.094	.078	100.00	70	42	7.10	12
.562	.312	SR-1	0.094	.094	100.00	64¼	29	6.425	12
.562	.250	SR-4	0.125	.062	245.00	64¼	118	9.05	12
.687	.437	SR-2	0.094	.125	75.00	55	15½	5.42	12
.687	.375	SR-5	0.125	.094	214.00	55	60	7.52	12
.687	.312	SR-10	0.156	.062	450.00	55	180	9.68	12
.812	.562	SR-3	0.094	.125	65.00	55	8.6	5.34	12
.812	.500	SR-6	0.125	.109	170.00	51¼	35	6.87	12
.812	.437	SR-11	0.156	.109	335.00	45¼	110	7.79	12
.812	.375	SR-16	0.187	.094	550.00	42¼	280	9.10	12
.937	.625	SR-7	0.125	.125	145.00	48	21½	6.35	12
.937	.562	SR-12	0.156	.109	275.00	45¼	44	7.50	12
1.062	.750	SR-8	0.125	.187	120.00	38½	18	5.075	6
1.062	.687	SR-13	0.156	.172	245.00	36¼	50	6.15	6
1.062	.625	SR-18	0.187	.156	400.00	35	120	7.00	6
1.062	.437	SR-23	0.25	.109	1200.00	33½	575	9.67	6
1.187	.875	SR-9	0.125	.250	100.00	32	14½	4.20	6
1.187	.812	SR-14	0.156	.187	220.00	35	45	5.80	6
1.187	.750	SR-19	0.187	.187	350.00	32	90	6.30	6
1.187	.562	SR-24	0.25	.125	1000.00	32	380	9.05	6
1.312	.937	SR-15	0.156	.250	290.00	29½	29	4.88	6
1.312	.875	SR-20	0.187	.187	300.00	32	65	6.25	6
1.437	1.000	SR-21	0.187	.312	270.00	24	60	4.63	6
1.562	1.125	SR-22	0.187	.312	240.00	24	42½	4.59	6
1.562	.937	SR-27	0.25	.203	650.00	26½	155	7.26	6
1.562	.203	SR-31	0.312	.187	1350.00	24	490	8.15	6
1.812	1.187	SR-28	0.25	.343	575.00	20¼	115	5.52	6
1.812	1.062	SR-32	0.312	.250	1150.00	21½	305	7.425	6
2.062	1.437	SR-29	0.25	.437	500.00	17½	85	4.77	6
2.062	1.312	SR-33	0.312	.297	1000.00	19¼	210	6.79	6
2.312	1.687	SR-30	0.25	.531	425.00	15½	65	4.18	6
2.312	1.562	SR-34	0.312	.406	850.00	16¼	160	5.75	6
2.562	1.812	SR-35	0.312	.437	750.00	16	115	5.45	6

Precision Punch and Plastics  
6100 Blue Circle Drive  
Minnetonka, MN 55343

Toll Free: (800) 227-0690  
Fax: (952) 935-5380  
Email: info@precisionpunch.com